

# DECLARATION OF PERFORMANCE



# ***Derome***

Timber

## **Machine strength graded structural timber**

### **Construction product**

Machine strength graded structural timber which fulfills the requirements according to EN 14081-1:2005+A1:2011. For further or more detailed information on the delivered product, in addition to what is given below, see information on the packaging or in possible accompanying commercial document.

### **Intended use of the construction product**

For load-bearing purposes in construction works designed according to Eurocode 5 (EN 1995) and for other uses where the strength and stiffness of the structure is essential.

### **Producer**

Company: Derome Timber AB, Okome  
Adress: Ätraforsvägen 25  
311 61 Okome  
Sweden  
Telephone: +46 340-666410  
E-mail: [timber@derome.se](mailto:timber@derome.se)  
Web site: [www.derome.se](http://www.derome.se)

### **System of assessment and verification of constancy of performance of the construction product**

System 2+.

### **Certification**

The notified body SP Technical Research Institute of Sweden (identification number 0402) has performed an initial inspection of the manufacturing plant and of the factory production control and performs continuous surveillance, assessment and evaluation of our factory production control. SP has issued EC Certificate of Factory Production Control No. 0402 – CPR – SC0391-09.

### **Declared performance**

Performance for machine strength graded structural timber in conformity with the harmonized European standard EN 14081-1:2005+A1:2011 Timber structures – Strength graded structural timber with rectangular cross section – Part 1: General requirements.

#### *Essential characteristics*

Species/species group

#### *Declared performance*


WPPA: spruce (*Picea abies*) and pine (*Pinus sylvestris*)

Growth area	NNE Europe (Northern and North Eastern Europe)
Range of thickness (fire resistance)	30 - 75 mm
Range of width (fire resistance)	60 - 300 mm
Surface finish	Sawn or planed
Dry or wet graded	Dry graded
Grading machine	Dynagrade n:o 100
Strength, stiffness and density	<i>Enligt EN 338: C30, C27, C24, C22, C20, C18, C16; Enligt EN 14081-4 eller relevant ITT-rapport: TR26;</i>
Durability	4 (according to EN 350-2)
Reaction to fire	D-s2, d0 (according to EN 14081-1, Table C.1)
Release of dangerous substances	No dangerous substance to be declared

That the performance for our construction product machine strength graded structural timber is in accordance with the declared performance given above is certified:

Okome 17-10-26.....  
(place and date of issue)

Derome Timber AB

  
.....  
(signature)

Sven Erik Dahlberg, Site Manager  
(name and function)